

123/1234 Hinge Options

Application	Hinge Cup	Optional Accuride 1234 Hardware Kit	Mfg. P/N	Door Thickness		Max. Tab		Min. Door Gap		Door Clearance	
Inset	35mm	4180-0391-XE	Salice 4180-0390-XE Supplied with 123 Self Close C2P7G33 3mm base BAR3P39	mm	inches	mm	inches	mm	inches	mm	inches
				19	3/4	8	5/16	0.7	1/32	1.0	1/32
				20.6	13/16	9.5	3/8			.9	
		N/A	Mepla Self Close DS05-253S/08 Free Swing DS05-153S/08	19	3/4	6	1/4	0.7	1/32	2	5/64
				20.6	13/16					0.4	1/64
			Blum Self Close 71M9650 Free Swing 70M9650 0mm Base 175H9100	19	3/4	8	5/16	2.2	3/32	5.5	7/32
				20.6	13/16					3.9	5/32
				22.2	7/8					2.3	3/32
				23.8	15/16					0.7	1/32
			Grass 1806VZ 3.5mm Base GHRZ 3.5/5.2/37 3mm spacer req'd for all doors	19	3/4	5	3/16	0.9	1/32	4	11/64
				20.6	13/16					2.4	3/32
				22.2	7/8					0.8	1/32
Inset for Thick Doors	40mm	4180-0313-XE	Salice Self Close CFA7P99 Free Swing CFA5P99 0mm Base BAR3P09	19	3/4	14	9/16	0.7	1/32	13	1/2
				20.6	13/16					11.4	7/16
				22.2	7/8					9.8	3/8
				23.8	15/16					8.2	5/16
				25.4	1					6.6	1/4
				27	1-1/16					5	3/16
				28.6	1-1/8					3.4	1/8
				30.2	1-3/16					2.0	1/16
				31.8	1-1/4					0.2	0
		N/A	Mepla Self Close DS25-253S/08 * Spacers req'd for doors 1" thick & over. 0mm Base DS 7250 ES37 00	19	3/4	6	1/4	0.7	1/32	5.5	7/32
				20.6	13/16					3.9	5/32
				22.2	7/8					2.3	3/32
				23.8	15/16					0.7	1/32
				25.4	1*	9	3/8			2.1	5/64
				27	1-1/16*					0.5	1/64
				28.6	1-1/8*					1.9	5/64
				30.2	1-3/16*	11	7/16	1.7	1/16	0.3	1/64
				Overlay Amount							
Overlay	40mm	4180-0314-XE	Salice Self Close CFA7G99 Free Swing CFA5G99 0mm Base BAR3P09	19	3/4	15	19/32	11.3	7/16	2	5/64
				20.6	13/16					0.4	1/64
		N/A	Mepla Self Close DS25-253S/08	19	3/4	11	7/16	5	3/16	5.5	7/32
				20.6	13/16					3.9	5/32
				22.2	7/8					2.3	3/32
				23.8	15/16					0.7	1/32

CAUTION: For doors under 36" tall, hinge carrier strip needs to be modified. Hinge carrier strip required for all doors.